Cardin

N17049
Cardinal RG

WINTERIZATION KIT MUST BE
REMOVED WHEN OUTSIDE
TEMPERATURE IS ABOVE 20°F
PILOT
COPILOT
GARMIN
121.200
112.80
108.10
STANDBY
ENR
GPS
NAV
MENU
CLR
ENT
TRAFFIC
TRK
MODE
STBY
122.800
109.60
117.30
STANDBY
1200
PRESSURE ALT
FL 008
MANIFOLD
PRESSURE
RPM
HOURS
VERTICAL SPEED
ALT
OBS
SBO
CARB HEAT

TruTrak II
N17049

N17049

WITH FANCY PANTS INSTALLED
SPINS PROHIBITED
N17049
WARNING
PITOT HEATER MUST BE
ON WHEN OPERATING
BELOW 40°F IN INSTRUMENT
METEOROLOGICAL CONDITIONS
WINTERIZATION KIT MUST BE
REMOVED WHEN OUTSIDE
TEMPERATURE IS ABOVE 20°F
VERTICAL SPEED
MANIFOLD PRESSURE
RPM
2376
HOURS
A/P DISC
ALT ENG/DISENG
Cardinal II
STATIC AIR
PULL ON

N17049
WARNING
PITOT HEATER MUST BE
ON WHEN OPERATING
BELOW 40°F IN INSTRUMENT
METEOROLOGICAL CONDITIONS
WINTERIZATION KIT MUST BE
REMOVED WHEN OUTSIDE
TEMPERATURE IS ABOVE 20°F
VERTICAL SPEED
MANIFOLD
PRESSURE
RPM
HOURS
cardinal II

cardinal II
1200

N17049

N17049
NAV COM 1
NAV COM 2
GPS
GPS
XPDR
ALT
ALT FIELD
FUEL PUMP
FLAP
LIGHTS
LAND

TruTach II
N17049
1200

N17049
WARNING
PITOT HEATER MUST BE
ON WHEN OPERATING
BELOW 40°F IN INSTRUMENT
METEOROLOGICAL CONDITIONS
cardinal II

TruTach II
N17049
ACQUIRING
1200
cardinal II

N17049

N17049
4505